DUAL BLADED RIBBING SAW Model DRS-270



The Jarvis Model DRS-270 pneumatically powered dual-bladed ribbing saw for quick, efficient rib cutting.

- The Model DRS-270 with two 9 inch (229 mm) blades and a full 2 hp motor for easy, quick and precise beef rib cutting.
- Lightweight, stainless steel construction only 29 lbs (13 kg), providing easy operator flexibility.





- Dual anti-tie down triggers for operator safety.
- 6.3 8.7 inch (160 221 mm) adjustable blade spread.
- 1.8 inch (46 mm) depth of cut.



DUAL BLADED RIBBING SAW Model DRS-270

Specifications		
Drive		Pneumatic
Model DRS-270		
Motor Power	2 hp	1500 W
Operating Pressure	90 psi	6.2 bar
Air Consumption at 90 psi	67 ft ³ / min	1.90 m ³ / min
Blade Speed		1150 rpm
Control Handle	Dual Trigger	Pneumatic
Blade Diameter	9.0 in	229 mm
Adjustable Blade Spread	6.3 - 8.7 in	160 - 221 mm
Cutting Depth (Maximum)	1.8 in	46 mm
Overall Length	22 in	559 mm
Weight	29 lbs	13 kg
Vibration	less than (<) 120 dB	$<1.0 \text{ m/sec}^2$
Noise (one meter from tool)		93.5 dB
Equipment Selection and Accessories		Order Number
Model DRS-270		
Saw, 9 in / 229 mm Blades, with Anti-tie Down Control Box 115 V		4001093
Saw, 9 in / 229 mm Blades, with Anti-tie Down Control Box, 220 V		4001092
Saw, 9 in / 229 mm Blades, without Controls		4001094
Air Filter / Regulator / Lubricator		3022003
Air Supply Hose Assembly		1059015

9 in / 229 mm diameter skip tooth blade - 72 teeth

1023102 4042037



Blade

Balancer