

# CIRCULAR BREAKING SAW

## Model SEC 180-3



**The Jarvis Model SEC 180-3 electrically powered circular breaking saw with indexing depth gage.**

**JARVIS**

- The SEC 180-3, with an adjustable 2.6 inch (66 mm) depth of cut, is ideally suited for:
  - Ribbing, ham marking, shoulder marking, chine bone cutting and removing contaminated back bones.
- Sealed, 1.9 hp electric motor for ultimate performance.
- Short overall length for maneuverability.
- Features mechanical motor braking.
- Smooth surface construction for easy cleaning and optimum hygiene.
- Meets national and international requirements for hygiene and safety.



**SMOOTH - POWERFUL - RUGGED**

# CIRCULAR BREAKING SAW

## Model SEC 180-3

### Specifications

Drive	Electric
-------	----------

#### Model SEC 180-3

Motor Power	1.9 hp	1400 W
Operating Voltage	575 / 460 / 380 / 230 / 208 V, 3 phase, 60 Hz	
	415 / 380 / 220 / 115 / 42 V, 3 phase, 50 Hz	

Blade Speed		
50 Hz		1375 rpm
60 Hz		1650 rpm

Control Handle	Electric
----------------	----------

Brake	Mechanical
-------	------------

Blade Diameter	7.1 in	180 mm
----------------	--------	--------

Cutting Depth (maximum)	2.6 in	66 mm
-------------------------	--------	-------

Overall Length	24 in	610 mm
----------------	-------	--------

Weight	30 lbs	13.6 kg
--------	--------	---------

### Equipment Selection and Accessories

### Order Number

Model SEC 180-3		
	42 V, 3 phase, 50 Hz*	4004168
	220 V, 3 phase, 50 Hz*	4004203
	460 V, 3 phase, 60 Hz*	4003213

Blade	<i>Please specify blade preference when ordering.</i>	
	7.1 in / 180 mm diameter- 98 teeth	1023439
	7.1 in / 180 mm diameter, Skip Tooth - 48 teeth	1023440

Balancer		4042037
----------	--	---------

\* For other configurations: please specify voltage, hertz and intended country of operation when ordering.



Products for the meat and poultry industry

Jarvis Products Corporation · 33 Anderson Road · Middletown, CT 06457-4926 · United States of America  
Telephone (860) 347-7271 · Fax (860) 347-9905 · sales@jarvisproducts.com · www.jarvisproducts.com