

CIRCULAR BREAKING SAW

Model SEC 230-2 / Model SEC 280-2



SEC 230-2



SEC 280-2

The Jarvis Models SEC 230-2 / SEC 280-2 - electrically powered circular breaking saws.

JARVIS

- The SEC 230-2, with a 3 inch (76 mm) depth of cut, and the SEC 280-2, with a 4 inch (102 mm) depth of cut are ideally suited for:
 - Beef or pork: cutting chucks, shoulders, ribs, forequarters, hindquarters, chine bones, briskets and loins.
- Double insulated, 2.4 hp electric motor for ultimate performance.
- Mechanical brake for 3 second blade stop.
- Switch is protected against moisture and dirt for sustained trouble-free operation.
- Lightweight and flexible - allows operators to work with meat that is hanging, or on the table.
- Meets national and international requirements for hygiene and safety.

SMOOTH - POWERFUL - RUGGED

CIRCULAR BREAKING SAW

Model SEC 230-2 / Model SEC 280-2

Specifications

Drive	Electric	
Model SEC 230-2 / SEC 280-2		
Motor Power	2.4 hp	1800 W
Operating Voltage	230 / 115 V, 1 phase, 50 or 60 Hz	
Blade Speed		1300 rpm
Control Handles	Single Trigger / Dual Handle	Electric
Brake		Mechanical
Blade Diameter		
SEC 230-2	9.1 in	231 mm
SEC 280-2	11.0 in	279 mm
Cutting Depth (maximum)		
SEC 230-2	3.0 in	76 mm
SEC 280-2	4.0 in	102 mm
Overall Length		
SEC 230-2	22.5 in	572 mm
SEC 280-2	30 in	762 mm
Weight		
SEC 230-2	22 lbs	10 kg
SEC 280-2	24 lbs	11 kg
Vibration	less than (<)123 dB	<1.3 m / sec ²
Noise		<85 dB

Equipment Selection and Accessories

Order Number

Model SEC 230-2 / SEC 280-2		
Model 230-2	115 V, 1 phase, 50 or 60 Hz*	4004234
Model 230-2	230 V, 1 phase, 50 or 60 Hz*	4004235
Model 280-2	115 V, 1 phase, 50 or 60 Hz*	4004237
Model 280-2	230 V, 1 phase, 50 or 60 Hz*	4004238
Blades <i>Please specify blade preference when ordering.</i>		
Model 230-2		
9.1 in / 231 mm diameter - 130 teeth		1023286
9.1 in / 231 mm diameter, Skip Tooth - 72 teeth		1023387
9.1 in / 231 mm diameter, Noise Reduction - random tooth spacing		1023299
9.1 in / 231 mm diameter, Noise Reduction - 60 teeth		1023348
Model 280-2		
11.0 in / 279 mm diameter - 150 teeth		1023288
11.0 in / 279 mm diameter, Skip Tooth - 78 teeth		1023388
11.0 in / 279 mm diameter - 72 teeth		1023393
11.0 in / 279 mm diameter, Noise Reduction - random tooth spacing		1023295
Balancer		4042037

* Other configurations available: please specify voltage, hertz and blade preference when ordering.



Products for the meat and poultry industry

Jarvis Products Corporation · 33 Anderson Road · Middletown, CT 06457-4926 · United States of America
 Telephone (860) 347-7271 · Fax (860) 347-9905 · sales@jarvisproducts.com · www.jarvisproducts.com