CIRCULAR BREAKING SAW Model SEC 230-4, SEC 230-4LN



The Jarvis Model SEC 230-4 - electrically powered circular breaking saw.



- The SEC 230-4, with a 3 inch (76 mm) depth of cut, is ideally suited for:
 - Beef: cutting chucks, shoulders, ribs, forequarters, hindquarters, chine bones, briskets and loins.
- Sealed, 2.25 hp electric motor for ultimate performance.
- Short overall length and specially designed handles for easy handling.
- Features electric or mechanical braking.
- Smooth surface construction for easy cleaning and optimum hygiene.
- Anti-tie down controls for operator safety.
- Meets national and international requirements for hygiene and safety.



CIRCULAR BREAKING SAW Model SEC 230-4, SEC 230-4LN

Specifications		
Drive		Electric
Model SEC 230-4, SEC 230-4LN		
Motor Power	2.25 hp	1678 W
Operating Voltage	415 / 400 / 230 / 115 / 4	•
Blade Speed	575 / 480 / 380 / 240 / 20	8 V, 3 phase, 60 Hz
50 Hz		1350 rpm
60 Hz		1650 rpm
Control Handle	Electric Dual Anti-tie Down or One Trigger (CE)	
Brake	Electric (DC) or Mechanical	
Blade Diameter	9.1 in	231 mm
Cutting Depth (maximum)	3.0 in	76 mm
Overall Length	24 in	610 mm
Weight	40 lbs	18.1 kg
Vibration	less than 108 dB	$< 0.25 \text{ m} / \text{sec}^2$
Noise (one meter from tool)		less than 80 dB
Equipment Selection and Accessories		Order Number
Model Sec 230-4		
42 V, 3 phase, 50 Hz w	rith DC brake	4004218
42 V, 3 phase, 50 Hz with mechanical brake		4004206
115 V, 3 phase, 50 Hz with mechanical brake		4004246
230 V, 3 phase, 50 Hz w		4004207
240 V, 3 phase, 60 Hz with mechanical brake		4004215
240 V, 3 phase, 60 Hz w		4004217
380 V, 3 phase, 50 Hz w		4004205
480 V, 3 phase, 60 Hz w		4004216
480 V, 3 phase, 60 Hz w	vith mechanical brake	4004214
Model Sec 230-4LN		
42 V, 3 phase, 50 Hz w		4004221
42 V, 3 phase, 50 Hz w		4004224
240 V, 3 phase, 60 Hz w		4004220
240 V, 3 phase, 60 Hz w		4004223
480 V, 3 phase, 60 Hz w		4004219
Hades Please specify blade pre		4004222
Blades <i>Please specify blade pre</i> 9.1 in / 231 mm diamete		1000006
		1023286 1023387
9.1 in / 231 mm diameter, Skip Tooth - 72 teeth 9.1 in / 231 mm diameter, Noise Reduction - random skip tooth		
	r, Noise Reduction - 60 teeth	1023348
Balancer	•	4042035



Products for the meat and poultry industry